


Model: SA5000





Oil pipe



Remote Control Key

Features:

- ♦ Durable, Overload, Operate Smoothly, Low Noise, Fast speed up & down
- ♦ Micro-control technology makes bollards work stable and reliable, Easy integrate to other systems
- ♦ Compatible with road barrier, Turnstiles and other access system control to achieve automatic control
- ♦ Advanced Hydraulic pressure technologies
- Remote control system realize wireless control up & down within 30 meters range
- ♦ Customized for different users requests
- ♦ Manual control hydraulic system devices
- ♦ Swiping card system: built-in card reader to control bollards up & down
- ♦ Road barrier integrate with Bollards : built-in access control realize road barrier, A/C and bollards in one-card.
- ♦ Connected with Computer Management OR Charging System

Securina Detection System Co., Limited.



Model: SA5000

♦ Technical Specification :

1 Control system: Industrial Grade hydraulic pump system

2 Min passing pressure: 80ton

3 Supply Voltage: 3phase/380V Control voltage 24V

4 System dynamic power (w): 5.5KW/3.7KW.

5 Rising speed: ≤3S (adjustable)

6 Dropping speed: ≤3S (adjustable)

7 Working temperature: -35°C~75°C

8 Storage temperature: -10°C~65°C, water-proof, damp-proof and dust-proof

9 Material: A3 steel, anti-rust paint, blade material: Stainless steel

10 Color: various(optional)

11 Dimension: L3000*W1000*H760

12 Weight: about 1.2 ton

13 Heavy duty hydraulic cylinder: HOB50-200CA+I

Parameters:

Full length: Standard 3m(max:6meters in option)

> Rising length: 2600mm,

Rising height: 500mm (can be customized)

➤ **Material Thickness:** 16mm

➤ **Supply Voltage:** 380V (Control voltage 24V)

Blade road blocker

> PLC: America Original Chip