

Under Vehicle Search Camera

Model: SA920


Features

- ➤ Horizontal 360 degree rotary camera to search surrounding.
- High-capacity lithium battery power supply, with long use time, and small size and light.
- With a 7 inch high resolution LCD display, the power consumption is less than 7W
- Micro wide-angle high definition camera, with infrared night vision capability, wider vision and clearer.
- Excellent design concepts based on this system, using two folding structure, the maximum opening angle of 180 degrees, can be pushed into the 1800mm deep caves
- ➤ Body is made of high strength Aluminum Alloy stamping molding
- > Operation is extremely labor-saving, easy to use
- > Carry bag packing, light and easy to carry, both portable and shoulder backpack.

Specifications:

Camera Angle: maximum horizontal angle is 355 degrees, The minimum horizontal angle is 22.5 degrees. Camera Focal distance: 3.6mm Camera Focal length: Wide-angle Camera Definition: 600 line and 1/3SONYCCD infrared image sensor, high definition with infrared night vision function. Power supply: SCM dedicated power charging and discharging technology to ensure the reliability of power supply products. Working environment temperature: -20°C to +60°C Working current: 400mA Monitor: 7 inch Color Display resolution: 800*480(RGB) Power: 6800mW Start-up time: ≤1.0s Total Weight: 3.4Kg Spreading length: 1780mm Folding length: 1020mm Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V Working time: 6-8 hours	Model NO.:	SA920
Camera Focal length:Wide-angleCamera Definition:600 line and 1/3SONYCCD infrared image sensor, high definition with infrared night vision function.Power supply:SCM dedicated power charging and discharging technology to ensure the reliability of power supply products.Working environment temperature:-20°C to +60°CWorking current:400mAMonitor:7 inch ColorDisplay resolution:800*480(RGB)Power:6800mWStart-up time:≤1.0sTotal Weight:3.4KgSpreading length:1780mmFolding length:1020mmPacking size:1050*210*310mmDisplay size:1020*180*280mmBattery capacity:5200AhWorking voltage:9-12.6V	Camera Angle:	
Camera Definition:600 line and 1/3SONYCCD infrared image sensor, high definition with infrared night vision function.Power supply:SCM dedicated power charging and discharging technology to ensure the reliability of power supply products.Working environment temperature:-20°C to +60°CWorking current:400mAMonitor:7 inch ColorDisplay resolution:800*480(RGB)Power:6800mWStart-up time:≤1.0sTotal Weight:3.4KgSpreading length:1780mmFolding length:1020mmPacking size:1050*210*310mmDisplay size:1020*180*280mmBattery capacity:5200AhWorking voltage:9-12.6V	Camera Focal distance:	3.6mm
high definition with infrared night vision function. Power supply: SCM dedicated power charging and discharging technology to ensure the reliability of power supply products. Working environment temperature: -20°C to +60°C Working current: 400mA Monitor: 7 inch Color Display resolution: 800*480(RGB) Power: 6800mW Start-up time: ≤1.0s Total Weight: 3.4Kg Spreading length: 1780mm Folding length: 1020mm Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Camera Focal length:	Wide-angle
technology to ensure the reliability of power supply products. Working environment temperature: -20°C to +60°C Working current: 400mA Monitor: 7 inch Color Display resolution: 800*480(RGB) Power: 6800mW Start-up time: ≤1.0s Total Weight: 3.4Kg Spreading length: 1780mm Folding length: 1020mm Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Camera Definition:	
Working current: 400mA Monitor: 7 inch Color Display resolution: 800*480(RGB) Power: 6800mW Start-up time: ≤1.0s Total Weight: 3.4Kg Spreading length: 1780mm Folding length: 1020mm Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Power supply:	technology to ensure the reliability of power supply
Monitor: 7 inch Color Display resolution: 800*480(RGB) Power: 6800mW Start-up time: ≤1.0s Total Weight: 3.4Kg Spreading length: 1780mm Folding length: 1020mm Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Working environment temperature:	-20°C to +60°C
Display resolution: 800*480(RGB) Power: 6800mW Start-up time: ≤1.0s Total Weight: 3.4Kg Spreading length: 1780mm Folding length: 1020mm Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Working current:	400mA
Power: 6800mW Start-up time: ≤1.0s Total Weight: 3.4Kg Spreading length: 1780mm Folding length: 1020mm Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Monitor:	7 inch Color
Start-up time:≤1.0sTotal Weight:3.4KgSpreading length:1780mmFolding length:1020mmPacking size:1050*210*310mmDisplay size:1020*180*280mmBattery capacity:5200AhWorking voltage:9-12.6V	Display resolution:	800*480(RGB)
Total Weight: 3.4Kg Spreading length: 1780mm Folding length: 1020mm Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Power:	6800mW
Spreading length: 1780mm Folding length: 1020mm Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Start-up time:	≤1.0s
Folding length: 1020mm Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Total Weight:	3.4Kg
Packing size: 1050*210*310mm Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Spreading length:	1780mm
Display size: 1020*180*280mm Battery capacity: 5200Ah Working voltage: 9-12.6V	Folding length:	1020mm
Battery capacity: 5200Ah Working voltage: 9-12.6V	Packing size:	1050*210*310mm
Working voltage: 9-12.6V	Display size:	1020*180*280mm
	Battery capacity:	5200Ah
Working time: 6-8 hours	Working voltage:	9-12.6V
	Working time:	6-8 hours

Securina Detection System Co., Limited.
Tel: +86-159-1416-2649 E-mail: sebrina@securinadetection.com





Application:

SA-920 is suitable using in airport security, parking inspection, military area inspection, personal private car inspection, sports, big events, local police stations, high-level hotels and large factories.etc



Securina Detection System Co., Limited.
Tel: +86-159-1416-2649 E-mail: sebrina@securinadetection.com